



ethernetgateway

DATA SHEET

Extend Network Coverage

Extend the WiMAC™ wireless signal by connecting this gateway anywhere on the local network. When connected, the pro wireless - ethernet gateway will coordinate connected wireless door controllers and feed the data back to the cloud node via a network. The ethernet gateway also gives you the ability to control doors in multiple buildings connected to the same network.



Model

PN: LZE

Specifications:

Communication

Ethernet
Encryption: AES 128bit
WiMAC™ Wireless Mesh (2.4 GHz / 802.15.4)
Wireless Range: 1 Mile LoS, 450ft indoor average

Environmental

Temperature: -20° ~ +60° C or -4° ~ +140° F
Humidity: 0 - 95% relative humidity non condensing

Enclosure

Dimensions (W x H x D) 2.75" x 3" x 1.125"
Metal Can

Weight

0.44 lbs (7.04 oz) W/O Antenna

Power

9 to 30V DC from included power supply

Included Items

Gateway, power supply, ethernet cable, and antenna

Manufacturer's Limited Warranty

One to three-year warranty against defects in materials and workmanship. For full details visit prodatakey.com.

Visit the ProdataKey dealer website support.pdk.io to access marketing, installation and support resources. For questions about the ethernet gateway, please contact support@prodatakey.com